SeeStation™

"Next Level Video Surveillance" SM

Custom PC Based DVRs - Analog and IP Surveillance Cameras - UTP A/V Trasnsmission & Conversion

High Tech High Quality High Value

Visit http://seestation.com

Distributed by PAM Distributing™

11413 E 58th Street

Tulsa, Ok. 74146

Local 918-252-0754 Toll Free 800-888-8101

Web Site http://www.pamdist.com

 # SS091021

© Copyright PAM Distributing 2009, all rights reserved, 11413 E 58th Street, Tulsa, Ok. 74146, 800-888-8101 www.pamdist.com

5 Configurations to Pick from:

3 for Home, Small Office, Small Business

BASIC

- 4 - 8 cameras
- up to 120 fps
- 250GB HD (Upgradable)
- Uses
  - Home Security
  - Small Offices
  - Small Stores

PRO

- 4 - 16 cameras
- up to 480 fps
- 500GB HD (Upgradable)
- Uses
  - Small Offices
  - Small Stores
  - Small Restaurants
  - Convenience Stores

PRO-LS

- 4 - 16 cameras
- up to 480 fps
- 1TB HD
- Uses
  - Small Offices
  - Small Stores
  - Small Restaurants
  - Convenience Stores

- Full Featured Windows Operating System provides maximum control over all system's functions'
- Pentiplex functionality allows simultaneous viewing of live, remote live, archived, remote archive, and extract archive without interrupting recording abiltiy
- Simple user interface (Novice computer users require little training)
- Simple and fast archive search and retrieval
- Control relay outputs on screen with mouse pointer
- Enhanced Proprietary MPEG-4 and/or H.264 high quality compression for small file sizes
- Remote monitoring for recording, playback, extraction, camera control, and more
- Can be configured into a website for remote viewing
- Multiple Custom camera views (from 1 to 16) Pre-alarm setting up to 10 seconds
- Set: user access, frame rate, and picture resolution per channel
- Archive file export is fast and easy in AVI Format to play in Microsoft Media Player
- Video archives time chart can be divided as low as 1 second increments or frame by frame for precise video retrieval
- Programmable Dynamic views
- Create and store unlimited custom views
- Spot monitor RCA output with real time raw live video
- Plug & Play camera detection
- Remote Client Preview mode with "Always on Top" option. Camera view stays on top of other applications
- Supports combined use of color and b/w cameras
- Up to 16 audio channel recording on all models
- Up to 16 alarm inputs and 16 relay outputs on all models

Depending on which software you choose, some features may vary.

© Copyright PAM Distributing LLC 2009, all rights reserved, 11413 E 58th Street, Tulsa, Ok. 74146, 800-888-8101 http://pamdist.com 10/29/09

5 Configurations to Pick from:

2 for Large Stores or Large Facilities

COMMERCIAL

- 8 - 32 cameras
- up to 960 fps
- 1.5TB HD (Upgradable)
- Uses
  - Retail Stores
  - Parts Stores
  - Grocery Stores
  - Warehouses

ENTERPRISE CASINO

- 8 - 64 cameras
- up to 1920 fps
- 4TB HD (Upgradable)
- Uses
  - Car Dealerships
  - Schools
  - Banks
  - Government Institutions

- Remote client provides log in for up to 16 different servers simultaneously
- Preprogramable views to view 64 different channels at 16 different locations on one screen
- Number of remote users virtually unlimited
- Complete password protection for all local and remote users. Feature by feature security provides each user access to only what they need.
- Hide specified cameras from specific users
- Set up of event, motion, or alarm recording per camera
- Recording may be set to manual 24/7 or triggered by motion, alarm, event, or schedule
- Motion detection sensitivity rate may be setup under motion detection function
- Motion masking allows user to set up specific area of camera view to trigger motion recording
- Multiple built in PTZ Dome Camera protocol including Pelco D through RS485 and Kalatel through RS422
- PTZ control by DVR software using USB Joystick/Keyboard/Mouse combination PTZ
- E-Map editor to import, export, and edit
- E-mail notification of alarm, event, or motion with optional screen shots included
- Multiple language menu support
- Network hardware support 10/100Base T
- Software support for static TCP/IP, DHCP, PPPoE & DDNS
- Allows for remote connection even to Dynamic IP addresses where static address is either not available or cost prohibitive
- Optional POS Module

© Copyright PAM Distributing LLC 2009, all rights reserved, 11413 E 58th Street, Tulsa, Ok. 74146, 800-888-8101 http://pamdist.com 10/29/09

PAM Distributing™
11413 E 58th Street
Tulsa, Oklahoma 74146, USA
Local 918.252.0754 **Toll Free** 800-888-8101
Confidential Price List 10-01-09
Visit http://seestation.com for detailed information on all these and other SeeStation Products

SeeStation™ "Next Level Video Surveillance" SM

Picture	Vendor Part Number	Description	IR Led	Water Proof	VF Lens	Power	3 Axis Mount
CCD Box Cameras							
	SS-359SN	1/3" SONY **Super-HAD** CCD,420TVL, 0.8 LUX F1.2 C/CS lens drive, **Day/Night** Price doesn't include lens, bracket and power adaptor	AGC AWB BLC EE /AI	NA	NA	DC 12V	NA
	SS-359SNH-2	1/3" SONY **Super-HAD** CCD, **540TVL** 0.5LUX F1.2 C/CS lens drive, **Day/Night** Price doesn't include lens, bracket and power adaptor.					
	SS-349SNH-1	1/3" Sony **Super-HAD** CCD, **520TVL** 0.5 LUX F1.2 **(HQ1)** C/CS lens drive, Price doesn't include lens, bracket and power adaptor.	NA	NA	NA	DC12V	NA
	SS-600	1/3" SONY CCD **540TVL** 0.1Lux F1.2 **0.001Lux F1.2 (SenseUP Mode)** **Line-lock Star-light** Dual Power 12VDC/24VAC	NA	NA	NA	Dual AC24V DC12V	NA
	SS-800	1/3" SONY **DSP 540TVL** 0.04Lux F1.2 **Super Wide Dynamic Range** - Typical 125dB Full Functionality for the Screen Menu. Internal and external (power) Sync Design. Dual Power 12VDC/24VAC	NA	NA	NA	Dual AC24V DC12V	NA
	SS-240	1/4" SONY Interline Transfer CCD 420TVL 0.5 Lux 30x Zoom 3.9-85.8mm Includes Remote Control & OSD Menu DC12V/750mA	NA	NA	NA	Dual AC24V DC12V	NA
	Camouflage Camera & Mini Camera						
New	**SS-149SA**	Extra Miniature Pinhole Color Camera 1/4" Sony CCD, 420TVL, 1.0LUX (Day)/ 0.05Lux (Night) 3.7mm cone pinhole lens DC 12V 100Ma	No	NA	No	DC 12V	No
	SS-M137-420P	1/3" Sony color CCD 420TVL 0.8 LUX 3.7mm pinhole lens	NA	NA	No	DC 12V	No
	SS-141S	1/3" Sony CCD 420TVL 1.0Lux/F1.2 Auto Gain Control, White Balance & Auto Back Light Compensation 3.6mm lens **Audio** **IP66 Weather Proof & Vandal Resistant** DC 12V	No	**IP66**	No	DC 12V	No
	HOT **SS-142SN**	1.5 Inch Plastic Mini Dome 1/3" Sony Super-HAD 420 TVL F1.2 3.6mm lens DC 12V	No	NA	No	DC 12V	No

© Copyright PAM Distributing LLC 2009, all rights reserved, 11413 E 58th Street, Tulsa, Ok. 74146, 800-888-8101 http://pamdist.com 10/29/09

Picture	Vendor Part Number	Description	IR Led	Water Proof	VF Lens	Power	3 Axis Mount
		Dome Cameras					
	SS-128SN HOT	1/3" SONY **Super-HAD** CCD 420TVL 1.0 LUX F1.2 3.6 mm lens DC 12V	No	NA	No	DC 12V	No
	SS-128F HOT	1/4" Sharp color CCD 420TVL 1.0 LUX F1.2 3.6mm lens DC 12V					
 3 Axis	**SS-D205SNH-2-W** White **SS-D205SNH-2-B** Black	1/3" Sony **540TVL 3.5-8mm Varifocal Lens** 3D Bracket With 4DIP Switch: AES, BLC, Mirror, AGC White or Black Case 12 V DC	No	NA	Yes	DC 12V	Yes
 3 Axis	**SS-R203SNA**	1/3" Sony color CCD 450TVL 0 Lux (F1.2 IR:on) **3.5-8mm Varifocal Lens** 15M IR distance, **17 Blue IR LEDs** DIP Switch Control Black Case, **DC12V/AC24V Dual Voltage**	Yes 15M	NA	Yes	DC 12/24V	Yes
	HOT **SS-D211SNA**	1/3" Sony CCD, 450TVL 0.1 Lux F1.2 **3.5-8mm Varifocal Lens** **3 Axis Brakcket** No IR DC12V White Case	No	**IP65**	Yes	12 VDC	Yes
 3 Axis	HOT **SS-IR211SNH-2**	1/3" Sony CCD, **540TVL** 0 Lux (F1.2 IR:on) **3.5-8mm Varifocal lens** **3 Axis Bracket** 20M IR Distance DC 12V Black Case.	Yes 20M	**IP65**	Yes	12 VDC	Yes
 3 Axis	HOT **SS-R204SNH-2A**	1/3" Sony color CCD **540TVL** 0 Lux (F1.2 IR:on) **3.5-8mm Varifocal lens** 15M IR distance DC12V/AC24V DIP Switch Control Indoor/Outdoor **Vandal Resistant**	Yes 15-20M	**IP55**	Yes	12/24 VCC/VAC	Yes
NEW 	**SS-IR213SN**	1/3″ SONY **Super HAD** CCD, 420 TVL Color 0.5Lux/F1.2, B/W 0.05Lux/F1.2, 0 Lux (F1.2 IR:on) **4-9MM Varifocal Lens** 15-20M IR Viewing Distance **3 Axis Bracket**, DIP switch control **Service Monitor plug In** Indoor/Outdoor Vandal Resistant DC 12V	Yes 15-20M	**IP55**	Yes	12 VDC	Yes
 3 Axis	**SS-IR213SNH-2**	1/3″ SONY **Super HAD** CCD, **540 TVL** Color 0.5Lux/F1.2, B/W 0.05Lux/F1.2, 0 Lux (F1.2 IR:on) **4-9MM Varifocal Lens** 15-20M IR Viewing Distance **3 Axis Bracket**, DIP switch control **Service Monitor plug In** Indoor/Outdoor **Vandal Resistant** DC 12V					
NEW 	HOT **SS-504F**	1/4" Sharp color CCD 420TVL 3.6mm lens 1.0 LUX F1.2 / 0 Lux (F1.2 IR:on) 15mm IR distance, **20 Blue IR LEDs** DC 12V	Yes 15M	NA	No	DC 12V	NA

© Copyright PAM Distributing LLC 2009, all rights reserved, 11413 E 58th Street, Tulsa, Ok. 74146, 800-888-8101 http://pamdist.com 10/29/09

Picture	Vendor Part Number	Description	IR Led	Water Proof	VF Lens	Power	3 Axis Mount
NEW New Case Design	HOT **SS-126NSNLL**	1/3" SONY Color CCD 420TVL **Star-light 0.05 LUX -- 0 Lux (F1.2 IR:on)** 3.6mm lens 20M IR Distance, **23 BLUE IR LEDs** White Indoor/Outdoor **Vandal Resistant** IP65 Case 12 VDC	Yes 20M	**IP55** **LP66**	No	DC-12V	NA
	HOT **SS-126NSNH-2LL**	1/3" SONY Color CCD **540TVL** **Star-light 0.05 LUX -- 0 Lux (F1.2 IR:on)** 3.6mm lens 20M IR Distance, **23 BLUE IR LEDs** White Indoor/Outdoor **Vandal Resistant** IP65 Case 12 VDC					
NEW New Case Design	HOT **SS-406NSNLL**	1/3" Sony Color CCD 420TVL **Star-light 0.05 LUX -- 0 Lux (F1.2 IR:on)** **4~9mm Varifocal Lens** (Exterior Adjustable) 30-40M IR Distance, **36 Blue IR LEDs**, IP55 - LP66 New Improved White Case Indoor/Outdoor **Vandal Resistant** 12 VDC	Yes 40M	**IP55** **LP66**	Yes	DC-12V	NA
	HOT **SS-406NSNH-2LL**	1/3" Sony Color CCD **540TVL** **Star-light 0.05 LUX -- 0 Lux (F1.2 IR:on)** **4~9mm Varifocal Lens** (Exterior Adjustable) 30-40M IR Distance, **36 Blue IR LEDs** New Improved White Case Indoor/Outdoor **Vandal Resistant** IP55 - LP66 12 VDC					
	SS-D406SNH-2	1/3" Sony Color CCD, **540TVL** 0 Lux (F1.2 IR:on) **6-15MM Varifocal Lens** (Exterior Adjustable) 40-50M IR Distance, **54 Blue IR LEDs**. IP55 Gray Case Indoor/Outdoor **Vandal Resistant** 12VDC	Yes 50M	**IP65** **LP66**	Yes	DC-12V	NA
	Bullet Cameras						
	HOT **SS-119SN**	1/3" Sony **Super HAD** CCD 420TVL 0 Lux (F1.2 IR:on) 3.6mm lens 25M IR Distance 30 PCS LED DC 12V	30pcs 25M	**IP55**	No	DC 12V	
	SS-119F	1/3" Sharp CCD 420TVL 0 Lux (F1.2 IR:on) 3.6mm lens 25M IR Distance 30 PCS LED DC 12V Includes Upgraded Mount (Not Shown)	30pcs 25M	**IP55**	No	DC 12V	
	HOT **SS-122SN**	1/3" SONY **Super HAD** CCD 420 TVL 0.1 LUX, 0 Lux (F1.2 IR:on) 3.6mm lens IP66, silver case 20M IR Distance 23 PCS LED DC 12V	23PCS 20 m	**IP66**	No	DC12V 300mA	NA
	SS-123SNH	1/3" SONY **Super HAD** CCD 480TVL 0.1 LUX, 0 Lux (F1.2 IR:on) 3.6mm lens IP66, silver case 30M IR Distance 30 PCS LED DC 12V	30PCS 25~30 M	**IP66**	No	DC12V 400mA	NA
	SS-123SNH-2	1/3" SONY **Super HAD** CCD **520 TVL,** 0.1 LUX, 0 Lux (F1.2 IR:on) 3.6mm lens IP66, silver case 30M IR Distance 30 PCS LED DC 12V					
NEW	HOT **SS-1139SNH**	1/3" Sony Color CCD 480TVL 0 Lux (F1.2 IR:on) 3.6mm Fixed lens 20M IR Distance 23 PCS LED White Case IP66 DC 12V	23EA 20M	**IP66**		DC12V	NA

© Copyright PAM Distributing LLC 2009, all rights reserved, 11413 E 58th Street, Tulsa, Ok. 74146, 800-888-8101 http://pamdist.com 10/29/09

Picture	Vendor Part Number	Description	IR Led	Water Proof	VF Lens	Power	3 Axis Mount
NEW New Mount Design	HOT **SS-1132NSN**	1/3" Sony CCD 420TVL 0 Lux (F1.2 IR:on) 3.6mm Lens 30M IR Distance 24 PCS LED Ivory Case With Improved Mount IP65 DC 12V	24 EA 30M	**IP65**	No	DC12V	NA
	HOT **SS-1132NSNH-2**	1/3" Sony CCD **540TVL** 0 Lux (F1.2 IR:on) 3.6mm Lens 30M IR Distance 24 PCS LED Ivory Case With Improved Mount IP65 DC 12V					
NEW	HOT **SS-1141SNH**	1/3" Sony Color CCD 480TVL, 0 Lux (F1.2 IR:on) **4-9mm Manual varifocal lens** **External Lens Adjustments** 30M IR Distance 36 PCS LED **Cable concealed inside of unique swivel bracket** IP66 DC 12V White Case	36EA 30M	**IP66**	Yes	DC12V	NA
	SS-1141SNH-2	1/3" Sony Color CCD **540TVL**, 0 Lux (F1.2 IR:on) **4-9mm Manual Varifocal Lens** **External Lens Adjustments** 30M IR Distance 36 PCS LED **Cable concealed inside of unique swivel bracket** IP66 DC 12V White Case					
NEW New Mount Design	HOT **SS-G1142SNH**	1/3" Sony color CCD 480TVL, 0.5 Lux, 0 Lux (F1.2 IR:on) **3.5~8mm Varifocal Lens** **External Lens Adjustments** 30M IR Distance 42 PCS LED **Cable concealed inside of unique swivel bracket** IP65, With Bracket DC 12V	42PCS 30m	**IP65**	Yes	DC12V 500mA	NA
	SS-1145SNH	1/3" Sony color CCD 480TVL, 0 Lux (F1.2 IR:on) **8~22mm Varifocal Lens** **External Lens Adjustments** 50M IR Distance 42 PCS LED Without Bracket DC 12V Requires Bracket SS-B06 Not Included	42PCS 50m	**IP65**	Yes	DC12V 500mA	NA
	Adjustable varifocal lens, with screws on base panel, camera with bracket,cable conceal inside of the bracket						
	HOT **SS-55SNA**	1/3" Sony color CCD 450TVL, 0 Lux (F1.2 IR:on) **4~9mm Varifocal lens** **External Lens Adjustments** 50M IR Distance **48 PCS Blue LED** IP55 DC 8-15V On Screen Display, White Case Bracket Included	48PCS 50M	**IP55**	Yes	DC12V	NA
	HOT **SS-55SNH-2A**	1/3" Sony color CCD **540TVL**, 0 Lux (F1.2 IR:on) **4~9mm Varifocal Lens** **External Lens Adjustments** 50M IR Distance **48 PCS Blue LED** IP55 DC 8-15V On Screen Display, White Case Bracket Included					
	SS-55 Circumgyrate horizontal 270 degrees, Cable conceal inside of the bracket, price includes the bracket						
	SS-513SNH	1/3" SONY CCD 480 TVL 0 Lux (F1.2 IR:on) **3.5~8mm Varifocal lens** **External Lens Adjustments** 30-40M IR Distance 48 PCS LED **Vandal Proof Indoor/Outdoor Criterion** IP65 Cable concealed inside of the bracket With Bracket DC 12V	48PCS 30-40M	**IP65**	Yes	DC12V 700mA	NA

© Copyright PAM Distributing LLC 2009, all rights reserved, 11413 E 58th Street, Tulsa, Ok. 74146, 800-888-8101 http://pamdist.com 10/29/09

Picture	Vendor Part Number	Description	IR Led	Water Proof	VF Lens	Power	3 Axis Mount
	DVR/Camera Kits						
	SS-5014VN-SN	4CH MJPEG DVR KIT Includes 4 Sets of SS-1139SN Sony Super HAD 1/3" CCD, 420TVL Camera Sets. Also includes Camera mounts, 4 each 100' Pre Made Siamese Video/Power Cables. Power Supply for Camera & DVR Included. ■ Real time recording, ■ CIF resolution. ■ Hard Drive Not Included	23EA 20M	**IP55**	No	DC 12V	NA
NEW	**SS-MDC-10**	DVR Dash Cam Video Output to AVI File VIA USB Cable (No Software Required) 25FPS, 1800MB/hour Video Resolution, VGA 640 x 480 Micro SD Cart (8G max) 12VDC w Built in Li-ion / 490mAH Includes AC & 12V Car Charge/.Adaptor	NA	NA	NA	12 VDC	NA
NEW	**SS-PJ-LED105**	LED Projector (Ultra High Brightness) 3500 lms Projection Distance 1.9 to 5m Resolution 800*600 support (1280*768 Lamp Model LEUWE3a-LED Contrast Ratio 1000:1 Size 300*250*109mm Weight 2.4kg	NA	NA	NA	110 VAC	NA
	Covert & Miniature Cameras						
	SS-PIR223SN Coming Soon	1/3" Sony CCD with 3.7mm pinhole lens 420TVL 0.8 LUX Working PIR Range is 5-6 meters DC12V	NA	NA	No	DC 12V	No
	SS-223SN Coming Soon	1/3" Sony color CCD 420TVL 0.8 LUX 3.7mm pinhole lens DC12V	NA	NA	No	DC 12V	No
	SS-223SNH-2 Coming Soon	1/3" Sony color CCD 540TVL 0.8 LUX 3.7mm pinhole lens DC12V	NA	NA	No	DC 12V	No
	SS-221SN	1/3" Sony Super-HAD CCD 420TVL 1.0 LUX 3.6mm lens	NA	NA	No	DC 12V	No
	SS-221SNH	1/3" Sony Super-HAD CCD 480TVL 1.0 LUX 3.6mm lens					
	WiFi Smart IP Cameras						
	SS-IP07B	**WIFI & SD, Lens & Power Adapter Included** 1/4" CMOS,1 Lux, 0 Lux (F1.2 IR:on), VGA, IR lights:10pcs, IR Distance: 10m, Built-in P/T, level :320° ; vertical :110°, with WIFI & SD function. H.264 3.6mm Lens	10 Pcs 10m	NA	Yes	DC 12V	NA
	Video Compression: H.264 baseline profile @ Level 2.2 Video Parameters: Brightness, hue, contrast, saturation and image quality Lens control (AI/EE, BLC, AGC, AWB) Stream format: Pure video stream or composite streams of audio and video		FREE	SeeStation Basic 32 Camera Software			

© Copyright PAM Distributing LLC 2009, all rights reserved, 11413 E 58th Street, Tulsa, Ok. 74146, 800-888-8101 http://pamdist.com 10/29/09

Picture	Vendor Part Number	Description	IR Led	Water Proof	VF Lens	Power	3 Axis Mount
	WiFi IP IR Dome Camera						
	SS-IP06ASN	Color 420TVL/BW 420TVL, 1/3" SONY CCD, 0.5 LUX, 0 Lux (F1.2 IR:on) Includes 3.6 Lens & DC 12V Power Adapter 10M IR Distance 16pc LED	16pcs 10-20m	NA	No	DC 12V	No
	H.264 D1,16 infrared LED's, infrared range 12m, Color: 0.3Lux, B&W: 0.01 Lux, Infrared: 0 Lux (F1.2 IR:on) Infrared LEDs, effective range up to10m-20m Video Frame Rate CCD; PAL; 1-25fps; NTSC; 1-30fps; CMOS; 1-25fps Supported Protocols: TCP, UDP, IP, HTTP, F		FREE	SeeStation Basic 32 Camera Software			
	WiFi H.264 Storage IP Box Camera						
	SS-IP02SN	1/3" SONY **Super HAD** CCD 420TVL 0.5 Lux F1.2	NA	NA	NA	DC 12V	NA
	WiFi H.264 Storage IP Box Camera PAL/NTSC 0.5Lux H.264 Baseline Profile @ Level 2.2 PAL:352*288(CIF), 704*288(2CIF), 704*576(D1); NTSC:352*240(CIF), 704*240(2CIF), 704*480(D1) G.726 Audio Compression Built-in Mic SD card slot Operation System:Microsoft Windows 98/ME/2000/XP		FREE	SeeStation Basic 32 Camera Software			
	H.264 Storage IP Box Camera						
	SS-IP01SN	1/3" SONY Color CCD 420TVL 0.5 Lux F 1.2 SD Card Slot DV 12V H.264 Baseline Profile @ Level 2.2 NTSC:352*240(CIF), 704*240(2CIF), 704*480(D1) NTSC:1-30 frames/second Network protocols: HTTP, TCP/IP, UDP, SMTP, PPPoE, DDNS, DNS, SNTP,DHCP, FTP,SNMP	NA	NA	NA	DC 12V	NA
	H.264 Storage IP Box Camera PAL/NTSC 0.5Lux H.264 Baseline Profile @ Level 2.2 PAL:352*288(CIF), 704*288(2CIF), 704*576(D1);NTSC:352*240(CIF), 704*240(2CIF), 704*480(D1) G.726 Audio Compression Built-in Mic SD card slot Operation System:Microsoft Windows 98/ME/2000/XP		FREE	SeeStation Basic 32 Camera Software			
	H.264 Dome IR Camera						
	SS-IP04SN	1/3" SONY **Super HAD** DSP CCD 420TVL 0.5 Lux, 0 Lux (F1.2 IR:on) 3.6m Lens -H.264 baseline profile @ Level 2.2 -Support dynamic IP address , LAN, Internet (ADSL and Cable Modem), Built-In-Mic	Yes 10-30M	NA	No	DC 12V	NA
	1/3" SONY Super HAD CCD 520TVL PAL/NTSC 0.5Lux H.264 Baseline Profile @ Level 2.2 PAL:352*288(CIF), 704*288(2CIF), 704*576(D1); NTSC:352*240(CIF), 704*240(2CIF), 704*480(D1) G.726 Audio Compression Built-in Mic Operation System:Microsoft Windows 98/ME/2000/XP/		FREE	SeeStation Basic 32 Camera Software			

© Copyright PAM Distributing LLC 2009, all rights reserved, 11413 E 58th Street, Tulsa, Ok. 74146, 800-888-8101 http://pamdist.com 10/29/09

Picture	Vendor Part Number	Description	IR Led	Water Proof	VF Lens	Power	3 Axis Mount
	High Speed Dome Cameras						
Genuine Sony Camera Module	**SS-457C**	1/4" Sony **Super HAD** CCD 480TVL **GENUINE Sony FCB-EX48CP** Day Night Camera Module 480TVL, 0.5LUX, Lens:4.1-73.8mm 216X Zoom, (18 X optical; 12 X digital)Color, OSD menu					
	SS-457E	1/4" Sony **Super HAD** CCD 480TVL **GENUINE Sony FCB-EX1010CP** Day Night Camera Module 480TVL, 0.5LUX, Lens: 4.1-95mm 312X zoom (36 X optical; 12 X digital)Color, OSD menu					
	Outdoor Speed Dome Built-in Decoders, Stepping Motor, 128 presets Alarm Function 7 alarm input / 2 alarm output, support alarm linkage Pan rotation range Continuous 360°, RS485, Manchester code, BI-BPASE code, as coaxial control Baud Rate (RS485) 2400/4800						
	SS-459	**Mini Speed** Dome Camera**,** 1/4" **500TVL Interline Transfer CCD** 0.7Lux (Color), 0.02Lux (B/W) **10X optical zoom, 10X digital zoom** **IR CUT Day/Night function** **OSD menu to set speed dome functions** 50 IRE Pelco-D, Pelco-P selectable F1.8, f=3.8~38mm 4 Patterns L Type J Type I Type	No	No	Yes	DC 12 or AC 24	NA
	SS-417	**3 Inch Mini Speed** Dome Camera 1/4" Samsung **Super HAD** CCD 480TVL (570TVL Night) 0.5 Lux **Effective Image (H X V) 380,000** **Zoom 10X, Zoom Length 4.2mm/42mm option** Pan rotation range 360° continuous rotation Built - in Decoders, 128 Presets , RS485/422 Bus	No	No	Yes		NA
	SS-KB100B	**Keyboard** for Speed Dome Camera **Features:** ■ Communication: RS485 ■ Protocol: PELCO-D, PELCO-P/4800Bps, PELCO-P/ 9600Bps, HUNDA600, Samsung ■ Control Up to 16 speed dome cameras					
	SS-KB100C	**Keyboard** for Speed Dome Camera **Features:** ■ Communication: RS485; ■ Protocol, Minking A01, Minking B01, Santachi, PELCO-D, PELCO-P/4800Bps, PELCO-P/9600Bps, PANASONIC, Longcomity, HUNDA600, LILIN, VICON, MOLYNX, KALATEL, VCL, ALEC					
	SS-KB200A	**Keyboard** for Speed Dome Camera **Features:** ■ Communication:Two way RS485 ■ Control numbers:Max 32 speed domes or Decoder ■ Embed multi-protocol ■ RS485 Control interface					

© Copyright PAM Distributing LLC 2009, all rights reserved, 11413 E 58th Street, Tulsa, Ok. 74146, 800-888-8101 http://pamdist.com 10/29/09

Picture	Vendor Part Number	Description	IR Led	Water Proof	VF Lens	Power	3 Axis Mount
	SS-KB200B	**3D Keyboard** for Speed Dome Camera Support PELCO matrix **Features:** ■ 2400/4800/9600/19200bps ■ Support PELCO matrix ■ Support 4 keyboards linkage, each keyboard can support 32 domes at most ■ Ergonomics design ■ LED with back-light, and display command menu					
	SS-KB200C	**Keyboard** for Speed Dome Camera **Features:** ■ Full Function Key Board ■ Camera Range 0-255 ■ On Screen display all functions ■ Zoom Display all functions ■ Video Multiplexer all functions ■ Baud Rates2400, 4800, 9600, 19200 ■ Signal RS-485 Multi port					
	Brackets & Power Adaptor						
	SS-M06	Full Direction Aluminum Mount					
	SS-M10	Pendant Mount for SS-PTZ-DN8000A					
	SS-M21	Wall Mount Bracket					
	SS-M22	Wall Mount Bracket					
	SS-M27	Universal Hoop/Pole Mount for SS-457C					
	SS-M28	Counter Mount for SS-457C					
	SS-M29	Universal Hoop/Pole Mount for SS-457C					

© Copyright PAM Distributing LLC 2009, all rights reserved, 11413 E 58th Street, Tulsa, Ok. 74146, 800-888-8101 http://pamdist.com 10/29/09

Picture	Vendor Part Number	Description	IR Led	Water Proof	VF Lens	Power	3 Axis Mount
	SS-PA08	Camera Power Supply 8 Camera 12V 10A					
	SS-AC02	Power Supply Narrow Design DC 12V, **1.15A**					
	SS-AC10	Power Supply, Standard Design DC 12V, **1.5A**					
	SS-AC20-4	12 VDC 2 Amp with 4 Male Plugs					
	SS-AC20-5	12 VDC 4 Amp with 1 Male Plug with Computer Style AC Power Cord					
	SS-PIGTAIL-1F4M	Single DC Jack to 4 DC PlugS, 1ft. Wire.					
	SS-DCPLUG-1	DC plug to removable terminal block. Small size for tight spaces. 2.1mm DC plug.					
	SS-PIGTAIL-M	Female DC Power Adapter Cord. (Pigtail connector) For easy installation and serviceability. Three-foot wire length.					
	SS-PIGTAIL-F	■ Male DC Power Adapter Cord. (Pigtail connector) ■ For easy installation and serviceability. ■ Three-foot wire length.					
	SS-DCPLUG-2	DC Connector with Terminal Block.					
	SS-DCPLUG-3	DC Plug-to-Plug Adapter.					
	SS-PIGTAIL-1F2M	Single DC Jack to Double DC Plug, 1ft. Wire.					
	SS-PIGTAIL-1F3M	Single DC Jack to Triple DC Plug, 1ft. Wire.					

© Copyright PAM Distributing LLC 2009, all rights reserved, 11413 E 58th Street, Tulsa, Ok. 74146, 800-888-8101 http://pamdist.com 10/29/09

Picture	Vendor Part Number	Description	IR Led	Water Proof	VF Lens	Power	3 Axis Mount
	SS-IR30	Waterproof IR Illuminator/30 meters					
	SS-IR80	Waterproof IR Illuminator/80 meters					
	SS-IR120	Waterproof IR Illuminator/120 meters/8 mm High Power LED					
	SS-IR160	Waterproof IR Illuminator/160 meters/8 mm High Power LED					

SeeStation™
"Next Level Video Surveillance" SM

SeeStation specializes in Digital Data Processing & Storage Systems. These systems with custom modifications are being married to a host of popular Digital Video Recording Hardware and Software. The results of this union are the most high quality AUDIO/VIDEO Digital Recording systems available anywhere. Each custom machine is hand assembled and thoroughly tested.

SeeStation has rapidly grown to include a wide range of DVRs, Surveillance Cameras, Surge Protection and Power Products. Popular additions include the Smart Technologies UTP Audio, Video, Data and Power Transmission Devices.

For more information about these high quality SeeStation products or other name brand products, call PAM Distributing Today.

PAM Distributing is currently seeking top quality Dealers, Integrators and Corporate Partners to assist with the See Station and other PAM Distributing Lines.

Call Us Today !

PAM DISTRIBUTING ™

Local: 918-252-0754 or Toll Free: 800-888-8101
or visit http://pamdist.com/

© Copyright PAM Distributing LLC 2009, all rights reserved, 11413 E 58th Street, Tulsa, Ok. 74146, 800-888-8101 http://pamdist.com 10/29/09

SeeStation Smart Technologies Cabling System Solutions

http://www.seestation.com/ For More Details

ITEM NO.	Product Description	Dealer
Twisted Pair Transmission		
Transceiver - Passive Series		
SEE-TTP111VTS	**Video Transceiver BNC Male to screw terminal built in Surge Protection (TVS)**	15.00
SEE-TTP111VCT	Weather Proof, Video Transceiver With Retractile Cord 18cm	13.00
SEE-TTP111VL	Weather Proof, Video Transceiver with 25cm mini coax	12.00
SEE-TTP111VLH	Video Transceiver With extra interference rejection, perfect to work with DVR	16.00
SEE-TTP111VP3	**Video & Power Transceiver (1 pair video) (1, 2 or 3 pair power)**	11.00
SEE-TTP111VPC	**Video & Power Transceiver Built in AC to DC12V Power Converter (1AMP)**	22.00
SEE-TTP111VPD	Video, Power, Data Transceiver, Terminal Connection	16.00
SEE-TTP111VPD - RJ45	Video, Power, Data Transceiver, RJ45 Connection	16.00
SEE-TTP111VK (DIY KITS)	SEE-TTP111VT+ SEE-TTP111VL KITS PACKAGE	22.80
SEE-TTP111VPK (DIY KITS)	SEE-TTP111VP+SEE-TTP111VPJ KITS PACKAGE **Transmit video & power over one networking cable**	22.80
SEE-TTP111VPK - T (Professioinal K	**(SEE-TTP111VP-T+SEE-TTP111VPJ-T) BNC TO Terminal Connection**	22.80
SEE-TTP414V	4 Channel Video Transceiver 4x BNC Female to 1 RJ-45 Female + 8 PIN Terminal block	30.00
Transceiver - Active Series		
SEE-TTA111AV	Video & Audio & Data Active Transceiver: SEE-TTA111AVT + SEE-TTA111AVR (power adapter included)	74.00
SEE-TTA111V	Video Active Transceivers : SEE-TTA111VT + SEE-TTA111VR (power adapter included)	70.00
SEE-TTA111VT	Video Transceiver - Active Transmitter (power adapter included)	33.00
SEE-TTA111VRH	Long Range Active Receiver Built in ground loop isolator (power adapter included)	56.00
SEE-TTA111VH	Active Receiver, extra interference rejection, color gain, surge protection (power adapter included)	84.00
SEE-TTA414VR	4 Channel Video Transceiver - Active Receiver (power adapter included)	156.00
Multi Channel in 1U Rack Panel		
SEE-TPP016D	**16 Port Passive Video & DATA Transceiver hub**	260.00
SEE-TPP016GB	**16 Port Passive Video Transceiver Hub Built in Hi Performance Ground Loop Isolator at each channel**	420.00
SEE-TPA008	8 Port Active Receiver Hub 1U PANEL, **Extra Interference Rejection** (power adapter included)	330.00
SEE-TPA008H	**8 Port Active Receiver Hub 1U PANEL, built in 16 output, surge protection (power adapter included)**	410.00
SEE-TPA016	16 Port Active Receiver Hub 1U PANEL, **Extra Interference Rejection** (power adapter included)	610.00
SEE-TPA016H	**16 Port Active Receiver Hub 1U PANEL, Built in 32 output, surge protection (power adapter included)**	750.00
Twisted Pair Video Distributor		
SEE-TDA102	Twisted Pair Distributor 1 IN 2 OUT (power adapter included)	56.00
CAT5 VGA Transmission		
SEE-KM01	Keyboard Mouse CAT5 Extender - PS/2 Interface (SEE-KMPT+SEE-KMPR)	24.00
SEE-KM02	Keyboard Mouse CAT5 Extender - USB Interface at local unit (SEE-KMPT+SEE-KMUR)	28.00
SEE-VKM01	VGA Keyboard Mouse CAT5 Extender - PS/2 Interface (SEE-VKMP x 2 pcs)	96.00
SEE-VKM02	VGA Keyboard Mouse CAT5 Extender - USB Interface (SEE-VKMP+SEE-VKMKUR)	100.00
SEE-TTP111VGA	CAT5 VGA Extender	78.00
SEE-AD001	Video to VGA Converter	56.00
SEE-AD001HN	**Hi Resolution Video to VGA Converter (BNC input to 1 xVGA and 1 x BNC output)**	84.00
Audio Transmission		
SEE-AA002	**Audio Pick up Box with 45cm power/audio cable (Microphohne to Power/Audio Cable)**	**14.40**
SEE-TTP111A-K	Analog Audio CAT5 Extender (2 pcs/ one set)	16.00
SEE-TTP212AV-K	Dual Video & Audio CAT5 Extender (2 pcs/ one set)	72.00
SEE-TDA109AV	CAT5 AV Distributor 1 in 9 out (power adapter included)	250.00
Coaxial Cabling Transmission		
Video Distributor		
SEE-CD102	1 Input to 2 Output Video Distributor (power adapter included)	20.00
SEE-CD102A	1 Input to 2 Output Video Distribution Amplifier (power adapter included)	34.00
SEE-CD104	1 Input to 4 Output Video Distributor (power adapter included)	34.00
SEE-CD108	1 Input to 8 Output Video Distributor (power adapter included)	48.00
SEE-CD408	4 Input to 8 Output Video Distributor (power adapter included)	78.00
Video Amplifier		
SEE-CA101	1 Input to 1 Output Video Amplifier (power adapter included)	30.00
SEE-CA101A	1 Input to 1 Output Video **with Audio Amplifier** (power adapter included)	34.00
Surge Protection Device		
Coaxial		
SEE-SP001	Coaxial Surge Protector for both CCTV, CATV use, BNC Connector	14.00
SEE-SP001P	**Power Surge Protection**	16.00
SEE-SP001VP	**Video & Power Surge Protector**	30.00
SEE-SP001VPD	**Video & Power, Data Surge Protector**	38.00
SEE-SP002	Coaxial Surge Protector for both CCTV, CATV use, F Connector	14.00
SEE-SP002VP	Video & Power Surge Protector, F Connector	30.00
SEE-SP016C (BNC Connector for Coax)	16 Channel Video Surge Protector for DVR In 1U Rack Mounting Panel(for coaxial cable use)	240.00
SEE-SP016T (Terminal Block for UTP)	16 Channel Video Surge Protector for DVR In 1U Rack Mounting Panel (for UTP cable use)	240.00

SeeStation Smart Technologies Cabling System Solutions

http://www.seestation.com/ For More Details

ITEM NO.	Product Description	Dealer
Solution Provide for Different Video Interference		
Video Ground Loop Isolator		
SEE-GL001	Coaxial Video Ground Loop Isolator , BNC male to BNC male with mini cable 30 cm	20.00
SEE-GL001H	**Hi Quality Coaxial Video Ground Loop Isolator , BNC male to BNC male with mini cable 30 cm**	36.00
SEE-GB001	Coaxial Video Ground Loop Isolator built in VIDEO BALUN,	24.00
SEE-TGP001	Twisted Pair Video Ground Loop Isolator, BNC male to screw terminal block	24.00
SEE-TGP001H	**Hi Quality Twisted Pair Video Ground Loop Isolator , BNC male to screw terminal block**	36.00
Video Transformer Filter		
SEE-CB001VH	Coaxial BALUN FOR DVR, Immunity DVR interference, BNC male to BNC male with mini cable 30 cm	18.00
High Frequency Interference Blocker		
SEE-CHB001H	**High Frequency Interference Blocker including SEE-CHB001HT+SEE-CHB001HR (power adapter included)**	96.00
Power Center		
SEE-AC02	**Power Supply Narrow Design DC 12V, 1.15A**	5.80
SEE-PC500	DC 12V, 1.15A	9.60
SEE-SWP124200	DC12V 4.2Amp Switching Power Supply	30.80

SeeStation Smart Home Audio Video

http://www.seestation.com/ For More Details

ITEM NO.	Product Description	Dealer
CAT5 Extender: Audio, Video, DVI,HDMI, VGA, Keyboard mouse, USB, RS232 , Wall Plate)		
SEE-AE01-T	Analog Audio CAT5 Extender - Terminal Termination 2pcs/1set	16.00
SEE-AE01D	Digital Audio CAT5 Extender 2pcs/1set	20.00
SEE-SE01A	S-Video & Audio CAT5 Extender 2pcs/1set	40.00
SEE-YE01	Component Video (YPbPr) CAT5 Extender 2pcs/1set	44.00
SEE-YE02D	Component Video & Digital Audio CAT5 Extender 2pcs/1set including power	184.00
SEE-HE01E	HDMI CAT5 Extender (1 in 1 out) 2pcs/1set **without power adapter**	96.00
SEE-TTP111RGB-K (SEE-TTP111RGB-RCA-K)	**Video Signal Transmitter (RED/GREEN/BLUE) (2 Piece Set) No Power Required**	60.00
CAT5 Distribution Amplifier & Extender		
SEE-YE09D	1 input 9 output Component Video & Digital Audio CAT5 Distribution Amplifier	300.00
SEE-YE02DR	**YE09D option model:** Component Video & Digital Audio CAT5 Receiver including power	96.00
Multimedia AV Distribution Amplifier		
SEE-HD02	1 input 2 output HDMI Distribution Amplifier	90.00
SEE-HD04	1 input 4 output HDMI Distribution Amplifier	150.00
Multimedia AV Switcher		
SEE-YS04A	4 input 2 output Component Video Switcher With Stereo Audio	98.00
SEE-YS04D	4 input 2 output Component Video With Digital/Optical Audio	104.00
SEE-HS02	2 input 1 output HDMI Switcher	60.00
SEE-HS04	4 input 1 output HDMI Switcher	84.00









PAM Distributing[tm]

11413 East. 58th St.
Tulsa, OK 74146
Phone: 918.252.0754
Toll Free: 800.888.8101
http://pamdist.com

Why SeeStation™?

Who can benefit from a **SeeStation™** *upgradable* system?

Homes
Convienence stores
Restaurants
Warehouses
Distributors
Car Dealerships
Schools

Small Businesses
Retail stores
Parts stores
Hobby shops
Grocery stores
Banks
Government Agencies

Any business, any size.

Every SeeStation video recording system can be custom configured for YOUR particular application! Not only that, it can expand and grow WITH your company.

Our DVR/NVR systems can support any analog camera and over 500 different models of IP security cameras. Every single one of our systems are thouroghly tested to run perfectly before you get it.

Our DVRs can run up to 64 channels with full IP, full Analog, or Hybrid.

Video Analysis - camera occlusions, lost signal, lose focus, foreign object, missing object, general motion.

POS and I/O Integration - Point of Sale and Trigger Activation Integrated into your system allows you to keep an eye on those you entrust with your company's everyday activities.

Popup E-map - Every one of our systems is able to show the location and direction of each camera connected to the system, which makes it simple and quick to find where an anomaly occurs, for quicker response times.

Triple Monitor Display - Our systems have the ability to watch live video, playback footage, and switch to and report abnormal events all on seperate monitors at the same time.

© Copyright PAM Distributing LLC 2009, all rights reserved, 11413 E 58th Street, Tulsa, Ok. 74146, 800-888-8101 http://pamdist.com 10/29/09